APPENDIX II

SANITARY SEWER LATI
AND
SANITARY SEWER CONNI

Before you Dig - Pennsylvania Act 187, Underground U
Requires You Call Pennsylvania One Ca

1. General – Sanitary sewer lateral shall include conn test tee, clean-outs, running trap with fresh air ven connection to the building drain. Down-spouts, rai drains, or french drains shall not be connected to the

2. Size - Residential - 4" minimum diameter pipe tha 1/4" per foot. Non-Residential - 6" minimum d minimum slope of 1/8" per foot.

3. Materials – The sanitary sewer lateral shall be Sched case of 6" pipe that may be SDR 35 or Schedule 40 same size as the sanitary sewer lateral with a vent shall be installed no less than two (2) and no more t of the outside wall. The pipe as it exits the building depth of 48". Vent pipes and clean-outs are not p cartpaths, walkways or other finished surface areas u Authority. The vent cap shall be installed 6" above into the sanitary sewer lateral.

   Food preparation establishments and other establ Authority shall install grease traps of a style and size in food preparation areas of these establishments shal

4. Clean-Outs and Directional Changes - Clean-outs, c curved fitting, riser pipe and a watertight cap are directional changes greater than 45 degrees. No 90 exceptions.

5. Adapters - Approved adapters as manufactured by F may be used to connect pipe joints, reduce 6" pipe to the running trap. All adapters shall be stainless ste steel clamps or must be encased in concrete.

6. Installation - Before digging the trench, the installe connection and the building drain. Trench width sha have uniform slope as near as possible at right angles