SANITAI

SANITARY

Before you Dig - Pennsylvania Act 18
Requires You Call Per

1. General – Sanitary sewer lateral s test tee, clean-outs, running trap connection to the building drain. drains, or french drains shall not b

2. Size - Residential - 4" minimum 1/4" per foot. Non-Residential minimum slope of 1/8" per foot.

3. Materials – The sanitary sewer lat case of 6" pipe that may be SDR 1 same size as the sanitary sewer la shall be installed no less than two of the outside wall. The pipe as it depth of 48". Vent pipes and cle cartpaths, walkways or other finish Authority. The vent cap shall be i into the sanitary sewer lateral.

   Food preparation establishments Authority shall install grease traps in food preparation areas of these e

4. Clean-Outs and Directional Chang curved fitting, riser pipe and a directional changes greater than 4 exceptions.

5. Adapters - Approved adapters as n may be used to connect pipe joints, the running trap. All adapters sha steel clamps or must be encased in

6. Installation - Before digging the connection and the building drain. have uniform slope as near as poss

LIMITS OF
MAINTENA
RESPONS

NOTE:
VENT PIPES AND CLE
ARE NOT PERMITTED
LOCATED IN DRIVEW
CARTPATHS, WALKW
PATIOS, PORCHES, O
OTHER FINISHED
SURFACE AREAS.

SIGHT TEE WITH
PVC SANITARY CAP,
CAST IRON COVER
AND LID STAMPED
"SEWER"

TO COLLECTOR SEW

4"x 4"x 4" OR 6"x
TEST TEE WITH PI
OR OBSERVATION
PORT AS SPECIFI

CONDENSED INSTALL

SANITARY SEWER LA
SERVICE CONNECTIO
SKILLED WORKMEN A
CUSTOMER IN ACCOR
OF THE RULES AND R
DETAILED SPECIFICA

RO
SE

Not to scale