## APPENDIX II

## SANITARY SEWER L
## AND
## SANITARY SEWER CO

Before you Dig - Pennsylvania Act 187, Undergroun
Requires You Call Pennsylvania One

1. General – Sanitary sewer lateral shall include c
test tee, clean-outs, running trap with fresh air
connection to the building drain. Down-spouts,
drains, or french drains shall not be connected to

2. Size - Residential - 4" minimum diameter pipe
1/4" per foot. Non-Residential - 6" minimu
minimum slope of 1/8" per foot.

3. Materials – The sanitary sewer lateral shall be S
case of 6" pipe that may be SDR 35 or Schedule
same size as the sanitary sewer lateral with a v
shall be installed no less than two (2) and no m
of the outside wall. The pipe as it exits the build
depth of 48". Vent pipes and clean-outs are n
cartpaths, walkways or other finished surface are
Authority. The vent cap shall be installed 6" ab
into the sanitary sewer lateral.

   Food preparation establishments and other es
Authority shall install grease traps of a style and
in food preparation areas of these establishments

4. Clean-Outs and Directional Changes - Clean-ou
curved fitting, riser pipe and a watertight cap
directional changes greater than 45 degrees. No
exceptions.

5. Adapters - Approved adapters as manufactured b
may be used to connect pipe joints, reduce 6" pip
the running trap. All adapters shall be stainless
steel clamps or must be encased in concrete.

6. Installation - Before digging the trench, the ins
connection and the building drain. Trench width
have uniform slope as near as possible at right an