APPENDIX II

SANITARY SEWER LAT
AND
SANITARY SEWER CONN

Before you Dig - Pennsylvania Act 187, Underground U
Requires You Call Pennsylvania One C

1. General – Sanitary sewer lateral shall include con test tee, clean-outs, running trap with fresh air ve connection to the building drain. Down-spouts, r drains, or french drains shall not be connected to th

2. Size - Residential - 4" minimum diameter pipe th 1/4" per foot. Non-Residential - 6" minimum minimum slope of 1/8" per foot.

3. Materials – The sanitary sewer lateral shall be Sch case of 6" pipe that may be SDR 35 or Schedule 4 same size as the sanitary sewer lateral with a vent shall be installed no less than two (2) and no more of the outside wall. The pipe as it exits the building depth of 48". Vent pipes and clean-outs are not cartpaths, walkways or other finished surface areas Authority. The vent cap shall be installed 6" above into the sanitary sewer lateral.

   Food preparation establishments and other estal Authority shall install grease traps of a style and si in food preparation areas of these establishments sh

4. Clean-Outs and Directional Changes - Clean-outs, curved fitting, riser pipe and a watertight cap a directional changes greater than 45 degrees. No 9(exceptions.

5. Adapters - Approved adapters as manufactured by may be used to connect pipe joints, reduce 6" pipe t the running trap. All adapters shall be stainless st steel clamps or must be encased in concrete.

6. Installation - Before digging the trench, the instal connection and the building drain. Trench width sl have uniform slope as near as possible at right angl