## APPENDIX I

## SANITARY SEWER I
## AND
## SANITARY SEWER CO

Before you Dig - Pennsylvania Act 187, Undergrou
Requires You Call Pennsylvania On

1. General – Sanitary sewer lateral shall include
test tee, clean-outs, running trap with fresh ai
connection to the building drain. Down-spout
drains, or french drains shall not be connected t

2. Size - Residential - 4" minimum diameter pip
1/4" per foot. Non-Residential - 6" minim
minimum slope of 1/8" per foot.

3. Materials – The sanitary sewer lateral shall be S
case of 6" pipe that may be SDR 35 or Schedul
same size as the sanitary sewer lateral with a
shall be installed no less than two (2) and no m
of the outside wall. The pipe as it exits the buil
depth of 48". Vent pipes and clean-outs are n
cartpaths, walkways or other finished surface ar
Authority. The vent cap shall be installed 6" ab
into the sanitary sewer lateral.

   Food preparation establishments and other e
Authority shall install grease traps of a style an
in food preparation areas of these establishments

4. Clean-Outs and Directional Changes - Clean-o
curved fitting, riser pipe and a watertight ca
directional changes greater than 45 degrees. N
exceptions.

5. Adapters - Approved adapters as manufactured
may be used to connect pipe joints, reduce 6" pi
the running trap. All adapters shall be stainles
steel clamps or must be encased in concrete.

6. Installation - Before digging the trench, the in
connection and the building drain. Trench widt
have uniform slope as near as possible at right a