APPENDIX II

SANITARY SEWER LA
AND
SANITARY SEWER CON

Before you Dig - Pennsylvania Act 187, Underground
Requires You Call Pennsylvania One (

1. General – Sanitary sewer lateral shall include co: test tee, clean-outs, running trap with fresh air v connection to the building drain. Down-spouts, : drains, or french drains shall not be connected to tl

2. Size - Residential - 4" minimum diameter pipe t 1/4" per foot. Non-Residential - 6" minimum minimum slope of 1/8" per foot.

3. Materials – The sanitary sewer lateral shall be Sc case of 6" pipe that may be SDR 35 or Schedule same size as the sanitary sewer lateral with a ver shall be installed no less than two (2) and no mor of the outside wall. The pipe as it exits the buildir depth of 48". Vent pipes and clean-outs are not cartpaths, walkways or other finished surface areas Authority. The vent cap shall be installed 6" abov into the sanitary sewer lateral.

   Food preparation establishments and other est Authority shall install grease traps of a style and s in food preparation areas of these establishments sl

4. Clean-Outs and Directional Changes - Clean-outs curved fitting, riser pipe and a watertight cap directional changes greater than 45 degrees. No 9 exceptions.

5. Adapters - Approved adapters as manufactured by may be used to connect pipe joints, reduce 6" pipe the running trap. All adapters shall be stainless s steel clamps or must be encased in concrete.

6. Installation - Before digging the trench, the insta connection and the building drain. Trench width have uniform slope as near as possible at right ang