APPENDIX

SANITARY SEWER
AND
SANITARY SEWER C

Before you Dig - Pennsylvania Act 187, Undergro
Requires You Call Pennsylvania C

1. General – Sanitary sewer lateral shall includ
test tee, clean-outs, running trap with fresh
connection to the building drain. Down-spou
drains, or french drains shall not be connected

2. Size - Residential - 4" minimum diameter pi
1/4" per foot. Non-Residential - 6" minir
minimum slope of 1/8" per foot.

3. Materials – The sanitary sewer lateral shall be
case of 6" pipe that may be SDR 35 or Sched
same size as the sanitary sewer lateral with a
shall be installed no less than two (2) and no
of the outside wall. The pipe as it exits the bu
depth of 48". Vent pipes and clean-outs are
cartpaths, walkways or other finished surface
Authority. The vent cap shall be installed 6"
into the sanitary sewer lateral.

   Food preparation establishments and other
Authority shall install grease traps of a style a
in food preparation areas of these establishmer

4. Clean-Outs and Directional Changes - Clean-
curved fitting, riser pipe and a watertight c
directional changes greater than 45 degrees. N
exceptions.

5. Adapters - Approved adapters as manufactured
may be used to connect pipe joints, reduce 6" p
the running trap. All adapters shall be stainle
steel clamps or must be encased in concrete.

6. Installation - Before digging the trench, the
connection and the building drain. Trench wi
have uniform slope as near as possible at right