## APPENDIX II

## SANITARY SEWER LAT
## AND
## SANITARY SEWER CONN

Before you Dig - Pennsylvania Act 187, Underground U
Requires You Call Pennsylvania One Ca

1. General – Sanitary sewer lateral shall include conn test tee, clean-outs, running trap with fresh air ven connection to the building drain. Down-spouts, rai drains, or french drains shall not be connected to the

2. Size - Residential - 4" minimum diameter pipe tha 1/4" per foot. Non-Residential - 6" minimum minimum slope of 1/8" per foot.

3. Materials – The sanitary sewer lateral shall be Sche case of 6" pipe that may be SDR 35 or Schedule 40 same size as the sanitary sewer lateral with a vent shall be installed no less than two (2) and no more of the outside wall. The pipe as it exits the building depth of 48". Vent pipes and clean-outs are not p cartpaths, walkways or other finished surface areas u Authority. The vent cap shall be installed 6" above into the sanitary sewer lateral.

   Food preparation establishments and other estab Authority shall install grease traps of a style and siz in food preparation areas of these establishments shal

4. Clean-Outs and Directional Changes - Clean-outs, curved fitting, riser pipe and a watertight cap are directional changes greater than 45 degrees. No 90 exceptions.

5. Adapters - Approved adapters as manufactured by may be used to connect pipe joints, reduce 6" pipe to the running trap. All adapters shall be stainless ste steel clamps or must be encased in concrete.

6. Installation - Before digging the trench, the install connection and the building drain. Trench width sh have uniform slope as near as possible at right angles