**APPE**

**SANITARY SE**
**A**
**SANITARY SEW**

Before you Dig - Pennsylvania Act 187, Un
Requires You Call Pennsylv

1. General – Sanitary sewer lateral shall i
test tee, clean-outs, running trap with
connection to the building drain. Dow
drains, or french drains shall not be con

2. Size - Residential - 4" minimum diam
1/4" per foot. Non-Residential - 6"
minimum slope of 1/8" per foot.

3. Materials – The sanitary sewer lateral sl
case of 6" pipe that may be SDR 35 or
same size as the sanitary sewer lateral
shall be installed no less than two (2) a
of the outside wall. The pipe as it exits
depth of 48". Vent pipes and clean-ou
cartpaths, walkways or other finished su
Authority. The vent cap shall be install
into the sanitary sewer lateral.

   Food preparation establishments and
Authority shall install grease traps of a
in food preparation areas of these establi

4. Clean-Outs and Directional Changes -
curved fitting, riser pipe and a watert
directional changes greater than 45 degr
exceptions.

5. Adapters - Approved adapters as manuf
may be used to connect pipe joints, redu
the running trap. All adapters shall be
steel clamps or must be encased in concr

6. Installation - Before digging the trench
connection and the building drain. Tren
have uniform slope as near as possible a