APPENDIX II

SANITARY SEWER LATERAL
AND
SANITARY SEWER CONNECTIO

Before you Dig - Pennsylvania Act 187, Underground Utility Li
Requires You Call Pennsylvania One Call 1-800

1. General – Sanitary sewer lateral shall include connection t test tee, clean-outs, running trap with fresh air vent, a gre connection to the building drain. Down-spouts, rain cond drains, or french drains shall not be connected to the sanitary

2. Size - Residential - 4" minimum diameter pipe that is inst 1/4" per foot. Non-Residential - 6" minimum diameter minimum slope of 1/8" per foot.

3. Materials – The sanitary sewer lateral shall be Schedule 40 s case of 6" pipe that may be SDR 35 or Schedule 40 solid c same size as the sanitary sewer lateral with a vent pipe an shall be installed no less than two (2) and no more than fiv of the outside wall. The pipe as it exits the building wall sh depth of 48". Vent pipes and clean-outs are not permitted cartpaths, walkways or other finished surface areas unless pr Authority. The vent cap shall be installed 6" above grade t into the sanitary sewer lateral.

   Food preparation establishments and other establishmen Authority shall install grease traps of a style and size accep in food preparation areas of these establishments shall also h

4. Clean-Outs and Directional Changes - Clean-outs, consistin curved fitting, riser pipe and a watertight cap are requir directional changes greater than 45 degrees. No 90 degree exceptions.

5. Adapters - Approved adapters as manufactured by Fernco, may be used to connect pipe joints, reduce 6" pipe to 4" and the running trap. All adapters shall be stainless steel shiel steel clamps or must be encased in concrete.

6. Installation - Before digging the trench, the installer shoul connection and the building drain. Trench width shall be ke have uniform slope as near as possible at right angles to the