APPENDIX II

SANITARY SEWER L
AND
SANITARY SEWER CO

Before you Dig - Pennsylvania Act 187, Undergroun
Requires You Call Pennsylvania One

1. General – Sanitary sewer lateral shall include c test tee, clean-outs, running trap with fresh air connection to the building drain. Down-spouts, drains, or french drains shall not be connected to

2. Size - Residential - 4" minimum diameter pipe 1/4" per foot. Non-Residential - 6" minimu minimum slope of 1/8" per foot.

3. Materials – The sanitary sewer lateral shall be S case of 6" pipe that may be SDR 35 or Schedule same size as the sanitary sewer lateral with a v shall be installed no less than two (2) and no m of the outside wall. The pipe as it exits the build depth of 48". Vent pipes and clean-outs are n cartpaths, walkways or other finished surface are Authority. The vent cap shall be installed 6" ab into the sanitary sewer lateral.

   Food preparation establishments and other e Authority shall install grease traps of a style and in food preparation areas of these establishments

4. Clean-Outs and Directional Changes - Clean-ou curved fitting, riser pipe and a watertight cap directional changes greater than 45 degrees. No exceptions.

5. Adapters - Approved adapters as manufactured b may be used to connect pipe joints, reduce 6" pip the running trap. All adapters shall be stainless steel clamps or must be encased in concrete.

6. Installation - Before digging the trench, the ins connection and the building drain. Trench width have uniform slope as near as possible at right an