APPENDI

SANITARY SEWE
AND
SANITARY SEWER

Before you Dig - Pennsylvania Act 187, Underg
Requires You Call Pennsylvania

1. General – Sanitary sewer lateral shall inclu
test tee, clean-outs, running trap with fresh
connection to the building drain. Down-sp
drains, or french drains shall not be connecte

2. Size - Residential - 4" minimum diameter
1/4" per foot. Non-Residential - 6" min
minimum slope of 1/8" per foot.

3. Materials – The sanitary sewer lateral shall
case of 6" pipe that may be SDR 35 or Sch
same size as the sanitary sewer lateral with
shall be installed no less than two (2) and n
of the outside wall. The pipe as it exits the
depth of 48". Vent pipes and clean-outs a
cartpaths, walkways or other finished surface
Authority. The vent cap shall be installed 6'
into the sanitary sewer lateral.

   Food preparation establishments and othe
Authority shall install grease traps of a style
in food preparation areas of these establishm

4. Clean-Outs and Directional Changes - Clea
curved fitting, riser pipe and a watertight
directional changes greater than 45 degrees.
exceptions.

5. Adapters - Approved adapters as manufactu
may be used to connect pipe joints, reduce 6'
the running trap. All adapters shall be stain
steel clamps or must be encased in concrete.

6. Installation - Before digging the trench, th
connection and the building drain. Trench v
have uniform slope as near as possible at rig