APPENDIX

SANITARY SEWER
AND
SANITARY SEWER C

Before you Dig - Pennsylvania Act 187, Undergro
Requires You Call Pennsylvania C

1. General – Sanitary sewer lateral shall include test tee, clean-outs, running trap with fresh a connection to the building drain. Down-spou drains, or french drains shall not be connected

2. Size - Residential - 4" minimum diameter pi 1/4" per foot. Non-Residential - 6" minin minimum slope of 1/8" per foot.

3. Materials – The sanitary sewer lateral shall be case of 6" pipe that may be SDR 35 or Sched same size as the sanitary sewer lateral with a shall be installed no less than two (2) and no of the outside wall. The pipe as it exits the bu depth of 48". Vent pipes and clean-outs are cartpaths, walkways or other finished surface a Authority. The vent cap shall be installed 6" a into the sanitary sewer lateral.

   Food preparation establishments and other Authority shall install grease traps of a style a in food preparation areas of these establishmen

4. Clean-Outs and Directional Changes - Clean- curved fitting, riser pipe and a watertight c directional changes greater than 45 degrees. N exceptions.

5. Adapters - Approved adapters as manufactured may be used to connect pipe joints, reduce 6" p the running trap. All adapters shall be stainle steel clamps or must be encased in concrete.

6. Installation - Before digging the trench, the i connection and the building drain. Trench wi have uniform slope as near as possible at right