APPE

SANITARY SE
A
SANITARY SEW

Before you Dig - Pennsylvania Act 187, Und
Requires You Call Pennsylva

1. General – Sanitary sewer lateral shall i
test tee, clean-outs, running trap with f
connection to the building drain. Dowr
drains, or french drains shall not be conn

2. Size - Residential - 4" minimum diame
1/4" per foot. Non-Residential - 6"
minimum slope of 1/8" per foot.

3. Materials – The sanitary sewer lateral sh
case of 6" pipe that may be SDR 35 or
same size as the sanitary sewer lateral
shall be installed no less than two (2) ar
of the outside wall. The pipe as it exits t
depth of 48". Vent pipes and clean-ou
cartpaths, walkways or other finished sur
Authority. The vent cap shall be installe
into the sanitary sewer lateral.

   Food preparation establishments and
Authority shall install grease traps of a s
in food preparation areas of these establis

4. Clean-Outs and Directional Changes - C
curved fitting, riser pipe and a waterti
directional changes greater than 45 degr
exceptions.

5. Adapters - Approved adapters as manufa
may be used to connect pipe joints, reduc
the running trap. All adapters shall be
steel clamps or must be encased in concre

6. Installation - Before digging the trench
connection and the building drain. Tren
have uniform slope as near as possible at