APPEN

SANITARY SEV
AN
SANITARY SEWE

Before you Dig - Pennsylvania Act 187, Und
Requires You Call Pennsylva

1. General – Sanitary sewer lateral shall in
test tee, clean-outs, running trap with fr
connection to the building drain. Down
drains, or french drains shall not be conne

2. Size - Residential - 4" minimum diamet
1/4" per foot. Non-Residential - 6" r
minimum slope of 1/8" per foot.

3. Materials – The sanitary sewer lateral sha
case of 6" pipe that may be SDR 35 or S
same size as the sanitary sewer lateral w
shall be installed no less than two (2) an
of the outside wall. The pipe as it exits th
depth of 48". Vent pipes and clean-out
cartpaths, walkways or other finished surf
Authority. The vent cap shall be installed
into the sanitary sewer lateral.

   Food preparation establishments and c
Authority shall install grease traps of a st
in food preparation areas of these establis

4. Clean-Outs and Directional Changes - C
curved fitting, riser pipe and a watertig
directional changes greater than 45 degre
exceptions.

5. Adapters - Approved adapters as manufac
may be used to connect pipe joints, reduce
the running trap. All adapters shall be s
steel clamps or must be encased in concre

6. Installation - Before digging the trench,
connection and the building drain. Trenc
have uniform slope as near as possible at