APPENDIX II

SANITARY SEWER LATERA
AND
SANITARY SEWER CONNECT

Before you Dig - Pennsylvania Act 187, Underground Utility
Requires You Call Pennsylvania One Call 1-

1. General – Sanitary sewer lateral shall include connectic test tee, clean-outs, running trap with fresh air vent, a connection to the building drain. Down-spouts, rain cc drains, or french drains shall not be connected to the sani

2. Size - Residential - 4" minimum diameter pipe that is 1/4" per foot. Non-Residential - 6" minimum diam minimum slope of 1/8" per foot.

3. Materials – The sanitary sewer lateral shall be Schedule case of 6" pipe that may be SDR 35 or Schedule 40 soli same size as the sanitary sewer lateral with a vent pipe shall be installed no less than two (2) and no more than of the outside wall. The pipe as it exits the building wall depth of 48". Vent pipes and clean-outs are not permi cartpaths, walkways or other finished surface areas unles Authority. The vent cap shall be installed 6" above grad into the sanitary sewer lateral.

   Food preparation establishments and other establishr Authority shall install grease traps of a style and size ac in food preparation areas of these establishments shall als

4. Clean-Outs and Directional Changes - Clean-outs, consi curved fitting, riser pipe and a watertight cap are rec directional changes greater than 45 degrees. No 90 degr exceptions.

5. Adapters - Approved adapters as manufactured by Ferno may be used to connect pipe joints, reduce 6" pipe to 4" a the running trap. All adapters shall be stainless steel sh steel clamps or must be encased in concrete.

6. Installation - Before digging the trench, the installer sh connection and the building drain. Trench width shall b have uniform slope as near as possible at right angles to t